

BioPlus 600/660D



Biostorage you can depend on



BioPlus 660D.
Drawers and glass door are optional extras.

The **BioPlus 600/660D** range is designed for the storage of the most delicate biomaterials, in situations where even tiny fluctuations in conditions inside the storage cabinet can have a serious effect on the contents.

BioPlus cabinets also enable you to reduce internal relative humidity, thus cutting down on any likelihood of undesirable contaminants getting near delicate biomaterials.

In terms of performance, these units are designed to provide the very best results even under exceptional conditions. The BioPlus utilises environmentally responsible HFC-free foam propellants and is available with HFC-free refrigerants.



The BioPlus 600/660D is available as a refrigerator or freezer in either white or stainless steel finish. All BioPlus models come with self-closing door. Glass door is available for refrigerator.



II 3G Ex nA nC nL IIB T2
TÜV 10 ATEX 354663

Biostorage
you can
depend on



BioPlus 600/660D



Biostorage you can depend on

Top panel with BioLine control unit

The MPC unit is specially developed for users of BioLine storage cabinets. Among its many features are acoustic temperature and door alarms, and a voltage-free contact (NO/NC) for remote alarms. The display can be easily locked.



Access port

24.5 mm port for ease of access, e.g. sensors for external temperature surveillance.




E-sensor

Extra sensor for providing a temperature reference within the storage compartment.



Shelves and drawers

A wide range of versatile interior fittings and layouts is available. The operating specifications and the interior layout can both be customised.



AIR DISTRIBUTION

The unique Gram BioLine air distribution system makes sure the temperature inside the cabinet remains stable at all times, while using the minimum amount of energy.

Stainless steel interior

The internal sides and bottom as well as shelf and drawer brackets and support rails are made of stainless steel.



ATEX

All BioPlus models comply with ATEX Cat.3 Zone 2 requirements, both internal and externally, allowing for placement in locations where explosive gas atmospheres may be present.



Technical Specifications	BioPlus ER600/660D	BioPlus RF600/660D
Temperature range	+20/-2 °C	-5/-25 °C
Ambient temperature range	solid door 10/43 °C; glass door (ER)10/38 °C	
Control Unit	Gram Control Unit with voltage-free contact, E-sensor, acoustic and visual door and temperature alarms that can be programmed individually, alarm recording and offset function.	
Material interior	Stainless steel	
Material exterior	White lacquered steel or stainless steel	
Dimensions mm (W x D x H)	600D: 695 x 876 x 1875/2125/ 660D: 695 x 876 x 1875/2125	
Gross volume	600D: 600 litres (21.2 cubic feet) / 660D: 660 litres (23.3 cubic feet)	
Net volume	600D: 432 litres (15.2 cubic feet) / 660D: 484 litres (17.1 cubic feet)	
Net weight	Unpacked net weight without optional fittings: 600: 146 kg / 660: 152 kg	
Modules for shelves and drawers	600D: Shelves 24 - Drawers 12 / 660D: Shelves 27 - Drawers 13	
Insulation	60 mm polyurethane with HFC-free cyclopentane propellant	
Refrigerant	R290 / R134a	R290 / R404A
Co ₂ e	R134a: 329	R404A: 902
Refrigeration capacity at -10 °C	R290 389 Watt / R134a 314 Watt	-
Refrigeration capacity at -25 °C	-	R290 475 Watt / R404a 568 Watt
Energy consumption	1.26 kWh/24h/1.18kWh/24h	4.03 kWh/24h/4.23 kWh/24h
Sound level	48,7 dB(A)	51,2 dB(A)
Base	Legs*	
Connection	230 V, 50 Hz	
Air system	Gram BioLine ventilated air distribution system	
Defrost system	Automatic smart defrost with re-evaporation of defrost water	

** The cabinets can also be delivered with castors or for mounting on a plinth at no extra charge